1 2

WHAT IS CLAIMED IS:

1	1.	A process for the generation of low nanosized particles of one
2	or more metals or th	e combusted products thereof, comprising:
3	a)	providing a multi-element diffusion flame burner having a
4		plurality of combustible gas passageways and combusting gas
5		passageways arranged in a geometric array defining a
6		substantially planar burner surface, and optionally, one or a
7		plurality of spaced apart precursor supply passageways;
8	b)	supplying non-premixed combusting gas to said combusting
9		gas passageways and non-premixed combustible gas to said
10		combustible gas passageways and igniting to form a primary
11		flame;
12	c)	introducing a particle precursor into at least one of
13		(i) said combusting gas,
14		(ii) said combustible gas, or
15		(iii) said precursor supply passageways, and
16	d)	recovering a nanosized combusted particle product.
1	2.	The process of claim 1, wherein said precursor comprises at
2	least one volatile metal compound of a metal of groups 3 to 7, a transition metal, or	
3	an inner transition m	netal.
1	3.	The process of claim 1, wherein said precursor comprises a
2	volatile metal alkyl,	metal alkoxide, metal hydride, metal halide, metal salt of an
3	organic carboxylic acid, metal glycolate, metal olefin complex, or a mixed metal	
4	compound containing at least one metal and two or more alkyl, alkoxide, hydride,	
5	halide, carboxylate,	olefin, or glycolate moleties.

4. The process of claim 1, wherein said metal comprises silicon, titanium, aluminum, zirconium, gold, silver, platinum, or tin.

1	5.	The process of claim 1, wherein said nanosized particles have
2	a mean particle size	of less than 50 nm.
1	6.	The process of claim 1, wherein said precursor is an organic
2		id nanosized particle product comprises one or more of Sn(0),
3	SnO, or SnO ₂ .	and analogue purchase product comprises one or more or one
1	7.	The process of claim 6, wherein said nanosized particle
2	product comprises S	n(0).
1	8.	The process of claim 1, wherein at least one of said
2		aid combustible gas is diluted with an inert gas.
1	9.	An Sn(0) or SnO nanosized particle product, prepared by the
2	process of claim 1.	
1	10.	The process of claim 1, further comprising
2	d)	altering the flame stoichiometry to vary the oxidation state of
3	said combusted product.	